

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
17 June 2004 (17.06.2004)


PCT

(10) International Publication Number
WO 2004/051173 A2

- (51) International Patent Classification⁷: **F28F**
- (21) International Application Number: **PCT/KR2002/002266**
2 June 04
- (22) International Filing Date: 2 December 2002 (02.12.2002)
- (25) Filing Language: English
- (26) Publication Language: English
- (71) Applicant (for all designated States except US): **LG ELECTRONICS INC. [KR/KR];** 20, Yoido-Dong Yongdunpo-Ku, Yongdunpo-Ku, 150-010 Seoul (KR).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): **LEE, Seong-Hwan [KR/KR];** Woosong Apt., 102-1303 Namyang-Dong, 641-091 Changwon, Kyungsangnam-do (KR). **CHO, Min-Chul [KR/KR];** 812-8, 2/3, Mandeok 1-Dong, Buk-Ku, 616-830 Busan (KR). **SHIN, Soo-Yeon [KR/KR];** Booyoung Apt. 1202-902 Wolsan maeul, Boogok-Li, Jangyu-Myeon, 621-833 Gimhae, Kyungsangnam-do (KR). **LEE, Sung-Hwa [KR/KR];** Towol Sungwon Apt., 503-402, Sangnam-Dong, 641-781 Changwon, Kyungsangnam-do (KR).
- (74) Agent: **PARK, Jang-Won;** Jewoo Bldg. 5th Floor 200 Nonhyun-Dong, Kangnam-Ku, 135-010 Seoul (KR).
- (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),

[Continued on next page]

(54) Title: **HEAT EXCHANGER OF VENTILATING SYSTEM**



(57) Abstract: A heat exchanger of a ventilating system, including heat exchange plates which are laminated at a predetermined interval, first vibration members which are laminated among the heat exchange plates, for generating turbulence in outdoor air passing through a first air path, being aligned in the first air path through which the outdoor air passes and second vibration members for generating turbulence in the indoor air passing through a second air path, while being aligned in the second air path through which indoor air passes, can improve heat transfer performance by increasing turbulence of air by positioning a mesh type heat exchange in a air path through which outdoor and indoor air passes.



Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,
ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, SI, SK,
TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ,
GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

- *without international search report and to be republished upon receipt of that report*

HEAT EXCHANGER OF VENTILATING SYSTEM

TECHNICAL FIELD

The present invention relates to a ventilating system for exchanging
5 indoor air and outdoor air and particularly, to a heat exchanger of a ventilating
system, capable of improving heat exchanging performance between outdoor
air and indoor air.

BACKGROUND ART

10 Generally, a ventilating system is a system for discharging polluted
indoor air to the outdoor and sucking fresh outdoor air to the indoor, and the
system includes an air cleaner for removing dust and foreign materials
contained in the outdoor air, and a heat exchanger for transferring heat of the
discharged indoor air to the sucked outdoor air.

15 Figure 1 is a perspective view showing a conventional ventilating system.

The ventilating system includes a case 2 which is mounted on a wall for
dividing indoor and outdoor, ventilating fans 4 and 6 which are mounted in the
case 2, for ventilating air which is sucked and discharged, an air cleaner (not
shown) which is installed in a portion to which the outdoor air inside the case 2
20 is sucked, for cleaning the outdoor air sucked to the indoor, and a heat
exchanger 8 which is positioned inside the case 2, for performing a heat
exchanging operation of indoor air discharged the outdoor and outdoor air
sucked to the indoor.

Here, the case 2 is disposed in a hole formed on the wall for diving the indoor and outdoor, and accordingly, one side is positioned indoors and the other side is positioned outdoors. At this time, an outdoor suction hole 10 to which outdoor air is sucked and an indoor discharging hole 12 through which indoor air is discharged to the outdoor are respectively formed on the side wall of the case 2 positioned outdoors, and an indoor discharging hole 14 through which outdoor air is discharged to the indoor and indoor suction hole 16 to which indoor air is sucked to the outdoor are respectively formed on the side wall of the case 2 positioned indoors.

The ventilating fans 4 and 6 includes a discharging blowing fan 4 which is installed in a position connected with the outdoor discharging hole 12, for providing a blowing pressure for discharging the indoor air to the outdoor, and a suction blowing fan 6 which is installed in a position connected with the indoor discharging hole 14, for providing a blowing pressure for sucking the outdoor air to the indoor.

Figure 2 is a perspective view showing a conventional heat exchanger of a ventilating system, and Figure 3 is a partial perspective view showing the conventional heat exchanger of a ventilating system.

The conventional heat exchanger 8 includes a plurality of base plates 20 which are laminated at a regular interval in a shape of a thin plate, first corrugation plates 22 which are respectively laminated in the spaces among the base plates 20, through which indoor air passes, and second corrugation plates 24 which are respectively laminated in the base plates 20 to be mutually

crossed with the first corrugation plates 22 in turn, through which outdoor air passes.

Here, the first and second corrugation plates 22 and 24 are curved in a triangular shape, and indoor and outdoor air passes to the inner and outer sides thereof, thus to mutually exchange heat.

Such heat exchanger 8 is formed in a rectangular shape by sequentially laminating the first corrugation plates 22, base plates 20, and second corrugation plates 24. The upper and lower surfaces of the heat exchanger 8 are respectively closed by the base plate 20, and the both side surfaces of the heat exchanger are connected with the outdoor suction hole 10 and indoor discharging hole 14, and outdoor air passes therethrough. Another both side surfaces of the heat exchanger are respectively connected with the outdoor discharging hole 12 and indoor suction hole 16, and indoor air passes therethrough.

That is, as the outdoor air which passes the first corrugation plates 22 and indoor air which passes the second corrugation plates 24 pass while being crossed with each other, heat exchange is performed by transferring heat of the indoor air through the base plates 20.

The operation of the conventional heat exchanger for the ventilating system with the above structure will be described as follows.

When the sucking blowing fan 6 is driven, the outdoor air is sucked to the outdoor suction port 10 and is supplied to the indoor through the indoor discharging hole 14 by passing the first corrugation plate 22. When the

discharging blowing fan 4 is driven, the indoor air is sucked through the indoor suction hole 16 and discharged to the indoor through the outdoor discharging hole 12 by passing the second corrugation plate 24.

Here, as the outdoor air passing in the first corrugation plate 22 and indoor air passing the second corrugation plate 24 flow while being crossed with each other, heat in the indoor air is transferred to the outdoor air through the base plate 20, and the outdoor air which sucked the heat of the indoor air is supplied to the indoor.

As described above, since heat in the discharged indoor air is sucked to the outdoor air and discharged to the indoor, rapid temperature change of the indoor air can be prevented in case of operating ventilation.

However, in the conventional heat exchanger of the ventilating system, the first and second corrugation plates 22 and 24 are formed in a shape of a plate having a corrugation of a predetermined shape, and a boundary layer S is developed as the air flowing in the first and second corrugation plates moves along from the inlet side to the outlet side. Therefore, heat transfer efficiency is degraded and indoor temperature is rapidly changed in case of ventilating since the outdoor air sucked to the indoor could not absorb heat in the indoor air. Also, energy consumption for recovering the indoor air is increased and indoor air conditioning performance is degraded.

That is, as shown in Figure 4, particles of viscous air which flow inside a pipe of the first and second corrugation plates 22 and 24 stick on the surface contacted on a surface of the inside of the pipe when the viscous air flows on

the surface of the inside of the pipe. As the air gets apart from the surface of the inside of the pipe, the air recovers the speed and gains a speed of a free flow in a position at a predetermined distance from the surface of the solid material. At this time, as the air is get apart from the surface of the inside of the pipe, a

5 boundary layer S is formed.

As described above, as the air flowing on the surface of the inside of the pipe is processed, the boundary layer is developed and the air gets apart from the surface of the inside of the pipe, thus to degrade heat transfer efficiency that the heat of the indoor air is transferred to the outdoor air through the base plate

10 20.

DISCLOSURE OF THE INVENTION

Therefore, an object of the present invention is to provide a heat exchanger of a ventilating system, capable of improving heat transfer performance by
15 restraining development of the boundary layer by increasing turbulence of outdoor and indoor air passing through the heat exchanger.

To achieve these and other advantages and in accordance with the purpose of the present invention, as embodied and broadly described herein, there is provided a heat exchanger of a ventilating system, including heat
20 exchange plates which are laminated at a predetermined interval, first vibration members which are laminated among the heat exchange plates, for generating turbulence in outdoor air passing through a first air path, being aligned in the first
~~air path~~ through which the outdoor air passes and second vibration members for

generating turbulence in the indoor air passing through a second air path, being aligned in the second air path through which indoor air passes.

The heat exchanger of the ventilating system includes first partitions which are respectively attached on the both side surfaces of the heat exchanger through which the outdoor air passes, for closing the side surface where the
5 second vibration member is aligned and second partitions which are respectively attached on the other both side surfaces of the heat exchanger through which the indoor air passes, for closing the side surface where the first vibration member is aligned.

10 The first and second vibration members include a fixing portion which is attached on the upper surface of the heat exchange plate, and a vibration portion which is curved at a predetermined angle from the fixing portion, for generating turbulence in the flowing air.

The first and second vibration members are formed with an elastic body
15 having a predetermined elasticity that the vibration portion is bent to the rear direction when the air is collided with a front surface thereof.

The first and second vibration members are formed with metal materials having a predetermined elasticity.

The first and second vibration members are formed with paper materials
20 having a predetermined elasticity.

The first and second vibration members are formed with plastic materials having a predetermined elasticity.

The first row vibration members are aligned on the upper surface of the

heat exchange plate at a predetermined interval, second row vibration members are aligned at the rear of the first row vibration members from at a predetermined interval from the first row vibration member, the first and second vibration members are repeatedly aligned at an identical interval, and the second row vibration member is positioned among the first row vibration members.

The interval among the vibration members of the first row portions and second row portions is $d1$ and the interval among the vibration members of the first row portions and second row portions is $d2$, the formula of $5 \leq d2/d1 \leq 10$ is satisfied.

10 If the width of the vibration members of the first row portions and second row portions is $L1$ and the width of the vibration members of the first row portions and second row portions is $L2$, the formula of $1 \leq L1/L2 \leq 5$ is satisfied.

If the thickness of the vibration members of the first row portions and second row portions is $t1$ and the thickness of the heat exchange plates is $t2$, the thickness of the first row portions and second row portions and the thickness of the heat exchange plates satisfy a formula of $0.5 \leq t2/t1 \leq 1$.

The foregoing and other objects, features, aspects and advantages of the present invention will become more apparent from the following detailed description of the present invention when taken in conjunction with the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

Figure 1 is a partially cut perspective view showing the structure of a

general ventilating system;

Figure 2 is a partial perspective view showing a conventional heat exchanger of a ventilating system;

Figure 3 is a perspective view showing a conventional corrugation plate
5 of the heat exchanger of a ventilating system;

Figure 4 is a cross-sectional view showing a movement of the air in the pipe to which the conventional heat exchanger of a ventilating system is supplied;

Figure 5 is a partial perspective view showing a heat exchanger of a ventilating system in accordance with the present invention;

10 Figure 6 is a partially disassembled perspective view showing the heat exchanger of the ventilating system in accordance with an embodiment of the present invention; and

Figure 7 is a cross-sectional view showing the heat exchanger of the ventilating system in accordance with the embodiment of the present invention.

15

MODES FOR CARRYING OUT THE PREFERRED EMBODIMENTS

Reference will now be made in detail to the preferred embodiments of the present invention, examples of which are illustrated in the accompanying drawings.

20 As the embodiment of the heat exchanger of the ventilating system in accordance with the present invention, there can be a plurality of them, and hereinafter, the most preferable one will be described.

Figure 5 is a perspective view showing a heat exchanger of a ventilating

system in accordance with the present invention.

With reference to Figure 1, in the ventilating system in accordance with the present invention, a case 2 is mounted to penetrate a wall which divides the indoor and outdoor, a side surface of the case 2 is positioned outdoors and the other side surface is positioned indoors. Here, an outdoor suction hole 10 through which the outdoor air is sucked and an outdoor discharging hole 12 through which the indoor air is discharged are respectively formed on a side surface positioned at the outdoor of the case 2, and an indoor discharging hole 14 through which the outdoor air is discharged to the indoor and an indoor suction hole 16 through which the indoor air is sucked are respectively connected on a side surface positioned at the indoor of the case 2.

A discharging blowing fan 4 for giving a blowing pressure for discharging the indoor air to the outdoor is installed in a position connected with the outdoor discharging hole 12 inside the case 2, and a suction blowing fan 6 for giving a blowing pressure for sucking the outdoor air to the indoor is installed in a position connected with the indoor discharging hole 14 inside the case 2.

An air cleaner (not shown) for removing foreign materials, dust and the like contained in the outdoor air is installed on the suction channel inside the case 2, and a heat exchanger 8 for transferring heat of the discharged indoor air to the sucked indoor air is installed inside the case 2.

As shown in Figure 5, the heat exchanger 8 includes heat exchange plates 50 which are laminated in a thin plate shape at a predetermined interval, first vibration members 54 which are attached among the heat exchange plates

50, for generating turbulence in the outdoor air passing through a first air path 52, being aligned in the first air path 52 through which outdoor air passes as plural, and second vibration members 58 for generating turbulence in the indoor air passing through a second air path 56, being aligned in the second air path 56 through which indoor air passes, as plural.

First partitions 60 for closing the second air path 56 are respectively attached on the both side surfaces of the heat exchanger 8 through which the outdoor air passes, and second partitions 62 for closing the second air path 56 are respectively attached on the other both side surfaces of the heat exchanger 8 through which the indoor air passes.

The first vibration member 54 and second vibration member 58 are attached in the direction that air passes, and is laminated in turn to be crossed with each other to generate turbulence in the air.

When describing the concrete shapes of the vibration members 54 and 58, as shown in Figure 6, The vibration members are formed in a shape of a thin plate which is composed of a fixing portion 66 which is attached on the upper surface of the heat exchange plate 50, and a vibration portion 68 which is curved at a predetermined angle from the fixing portion 66, for generating turbulence in th for

turbulence in thable that the fixing portion 66 is attached by using an adhesive on the upper surface of the heat exchange plate 50, and the method can be any method that can attach the fixing portion 66 on the upper surface of the heat exchange plate 50.

Such vibration members 54 and 58 are formed as an elastic body having a predetermined elasticity that the vibration portion 68 is bent to the rear direction when air is collided with the front surface thereof, and more definitely, it is desirable that the members are formed with thin aluminum materials or paper materials.

Also, the vibration members 54 and 58 can be manufactured with plastic materials such as the polyethylene or polypropylene.

The vibration members 54 and 58 include first row portions 70 which are aligned at a predetermined interval on the upper surface of the heat exchange plate 50, and second row portion 72 which are aligned at a predetermined interval from the first row portion 70 at the rear of the first row portion 70, and the vibration members are composed by repeating a predetermined number of the second row portion 72 repeatedly aligned in spaces among the first row portions.

Here, it is desirable that the interval $d1$ among the vibration members of the first row portions 70 and second row portions 72 and the interval $d2$ among the vibration members of the first row portions 70 and second row portions 72 are aligned so that they satisfy the formula of $5 \leq d2/d1 \leq 10$. In addition, it is desirable that the width $L2$ and length $L1$ of the vibration members satisfy the formula of $1 \leq L1/L2 \leq 5$.

It is desirable that the thickness $t1$ of the vibration members and the thickness $t2$ of the heat exchange plates satisfy the formula of $0.5 \leq t2/t1 \leq 1$.

The operation of the heat exchanger of the ventilation system in accordance with an embodiment of the present invention with the above structure

will be described as follows.

Figure 7 is a view showing operational status of the air passing through the heat exchanger in accordance with the embodiment of the present invention.

When the suction blowing fan 6 is driven, the outdoor air is sucked
5 through the outdoor suction hole 10 and various dusts and foreign materials are removed passing through the air cleaner, and the air is supplied to the indoor by passing the first air path 52 through the indoor discharging hole 14. When the discharging blowing fan 4 is driven, the indoor air is sucked through the indoor suction hole 16, and is discharged into the outdoor by passing the second air path
10 through the outdoor discharging hole 12.

Here, as the indoor air passing through the first air path 52 and the outdoor air passing through the second air path 56 flow while being crossed with each other centering around the heat exchange plate 50, heat contained in the indoor air is sucked to the outdoor air through the heat exchange plate 50, and
15 the completely heat-exchanged outdoor air is supplied to the indoor.

In the operation of the heat exchanger, the outdoor air is collided with the surfaces of the first vibration members 58 and dispersed in all directions. Therefore, heat transfer performance to the heat exchange plate 50 can be improved as the air flows in contact with the surface of the heat exchange plate
20 50. As the indoor air flowed to the second air path 56 is dispersed in all directions, while being collided with the surface of the second vibration member 58 and flows in contact with on the surface of the heat exchange plate 50, thus to improve heat transfer performance to the heat exchange plate 50.

As the present invention may be embodied in several forms without departing from the spirit or essential characteristics, it is to be understood that the above-described embodiments are not limited by any of the details of the foregoing description, unless otherwise specified, but rather should be construed broadly within its spirit and scope as defined in the appended claims, and therefore all changes and modifications that fall within the metes and bounds of the claims, or equivalence of such metes and bounds are therefore intended to be embraced by the appended claims.

INDUSTRIAL APPLICABILITY

In the heat exchanger of the ventilating system in accordance with the present invention with the above structure, turbulence of the outdoor and indoor air can be increased by the operation of the first and second vibration members by attaching the first vibration member on the first air path through which the outdoor air passes and the second vibration member in the second air path through which the indoor air passes, and accordingly, the heat transfer performance can be improved by restraining development of a boundary layer.

Also, since the heat transfer performance of the heat exchanger is excellent, the indoor temperature can be uniformly maintained. Accordingly, the indoor environment can be made to be comfortable, and energy consumption can be reduced by minimizing the change of the indoor temperature.

CLAIMS

1. A heat exchanger of a ventilating system, comprising:
heat exchange plates which are laminated at a predetermined interval;
first vibration members which are laminated among the heat exchange
5 plates, for generating turbulence in outdoor air passing through a first air path,
being aligned in the first air path through which the outdoor air passes; and
second vibration members for generating turbulence in the indoor air
passing through a second air path, being aligned in the second air path through
which indoor air passes.

10 2. The exchanger of claim 1, further comprising:
first partitions which are respectively attached on the both side surfaces
of the heat exchanger through which the outdoor air passes, for closing the side
surface where the second vibration member is aligned; and
15 second partitions which are respectively attached on the other both side
surfaces of the heat exchanger through which the indoor air passes, for closing
the side surface where the first vibration member is aligned.

20 3. The exchanger of claim 1, wherein the first and second vibration
members include a fixing portion which is attached on the upper surface of the
heat exchange plate, and a vibration portion which is curved at a predetermined
angle from the fixing portion, for generating turbulence in the flowing air.

4. The exchanger of claim 3, wherein the first and second vibration members are formed with an elastic body having a predetermined elasticity that the vibration portion is bent to the rear direction when the air is collided with a front surface thereof.

5

5. The exchanger of claim 3, wherein the first and second vibration members are formed with metal materials having a predetermined elasticity.

6. The exchanger of claim 3, wherein the first and second vibration members are formed with paper materials having a predetermined elasticity.

10

7. The exchanger of claim 3, wherein the first and second vibration members are formed with plastic materials having a predetermined elasticity.

15

8. The exchanger of claim 3, wherein first row vibration members are aligned on the upper surface of the heat exchange plate at a predetermined interval, second row vibration members are aligned at the rear of the first row vibration members from at a predetermined interval from the first row vibration member, the first and second vibration members are repeatedly aligned at an identical interval, and the second row vibration member is positioned among the first row vibration members.

20


9. The exchanger of claim 8, wherein if the interval among the vibration


members of the first row portions and second row portions is $d1$ and the interval among the vibration members of the first row portions and second row portions is $d2$, the formula of $5 \leq d2 / d1 \leq 10$ is satisfied.

5 10. The exchanger of claim 8, wherein if the width of the vibration members of the first row portions and second row portions is $L1$ and the width of the vibration members of the first row portions and second row portions is $L2$, the formula of $1 \leq L1 / L2 \leq 5$ is satisfied.

10 11. The exchanger of claim 8, wherein if the thickness of the vibration members of the first row portions and second row portions is $t1$ and the thickness of the heat exchange plates is $t2$, the thickness of the first row portions and second row portions and the thickness of the heat exchange plates satisfy a formula of $0.5 \leq t2 / t1 \leq 1$.

1/6
FIG. 1



2/6
FIG. 2

3/6

FIG. 3








FIG. 4



4/6
FIG. 5

5/6
FIG. 6

6/6
FIG. 7



(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
17 June 2004 (17.06.2004)

PCT

(10) International Publication Number
WO 2004/051173 A3

(51) International Patent Classification⁷: **F28D 9/00**,
F28F 13/02, 13/12, F24F 7/08, 12/00

(21) International Application Number:
PCT/KR2002/002266

(22) International Filing Date: 2 December 2002 (02.12.2002)

(25) Filing Language: English

(26) Publication Language: English

(71) Applicant (for all designated States except US): **LG ELECTRONICS INC.** [KR/KR]; 20, Yoido-Dong Yongdunpo-Ku, Yongdunpo-Ku, 150-010 Seoul (KR).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **LEE, Seong-Hwan** [KR/KR]; Wooseong Apt., 102-1303 Namyang-Dong, 641-091 Changwon, Kyungsangnam-do (KR). **CHO, Min-Chul** [KR/KR]; 812-8, 2/3, Mandeok 1-Dong, Buk-Ku, 616-830 Busan (KR). **SHIN, Soo-Yeon** [KR/KR];

Booyoung Apt. 1202-902 Wolsan maeul, Boogok-Li, Jangyu-Myeon, 621-833 Gimhae, Kyungsangnam-do (KR). **LEE, Sung-Hwa** [KR/KR]; Towol Sungwon Apt., 503-402, Sangnam-Dong, 641-781 Changwon, Kyungsangnam-do (KR).


(74) Agent: **PARK, Jang-Won**; Jewoo Bldg. 5th Floor 200 Nonhyun-Dong, Kangnam-Ku, 135-010 Seoul (KR).

(81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),

[Continued on next page]

(54) Title: HEAT EXCHANGER OF VENTILATING SYSTEM



(57) Abstract: A heat exchanger (8) of a ventilating system, including heat exchange plates (50) which are laminated at a predetermined interval, first vibration members (54) which are laminated among the heat exchange plates (50), for generating turbulence in outdoor air passing through a first air path (52), being aligned in the first air path through which the outdoor air passes and second vibration members (58) for generating turbulence in the indoor air passing through a second air path (56), while being aligned in the second air path (56) through which indoor air passes, can improve heat transfer performance by increasing turbulence of air by positioning a mesh type heat exchange in a air path through which outdoor and indoor air passes.



Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,
ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, SI, SK,
TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ,
GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

— *with international search report*

(88) Date of publication of the international search report:

10 March 2005

INTERNATIONAL SEARCH REPORT

International application No.
PCT/KR 2002/002266

CLASSIFICATION OF SUBJECT MATTER

IPC⁷: F28D 9/00; F28F 13/02 13/12; F24F 7/08 12/00

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC⁷: F28D, F28F, F24F

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

WPI PAJ EPODOC KIPRIS

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	JP 10 122787 A (HONDA MOTORS CO.) 15 May 1998 (15.05.1998) <i>figs 2, 5, 6 and 7 with description.</i>	1-2
Y	FR 2804471 A (BEHR GmbH) 3 August 2001 (03.08.2001) <i>figs. 1 and 8 with description.</i>	1-2
A	SU 556311 A (ODESSA REFRIG) 30 April 1977 (30.04.1977) <i>abstract, fig. 3.</i>	1-11

☐ Further documents are listed in the continuation of Box C.

☒ See patent family annex.

* Special categories of cited documents:

- „A“ document defining the general state of the art which is not considered to be of particular relevance
- „E“ earlier application or patent but published on or after the international filing date
- „I“ document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- „O“ document referring to an oral disclosure, use, exhibition or other means
- „P“ document published prior to the international filing date but later than the priority date claimed

- „T“ later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- „X“ document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- „Y“ document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
- „&“ document member of the same patent family

Date of the actual completion of the international search

3 December 2004 (03.12.2004)

Date of mailing of the international search report

21 December 2004 (21.12.2004)

Name and mailing address of the ISA/AT

Austrian Patent Office
Dresdner Straße 87, A-1200 Vienna

Facsimile No. 1/53424/535

Authorized officer

SCHLECHTER B.

Telephone No. 1/53424/448

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No.

PCT/KR 2002/002266

Patent document cited in search report			Publication date	Patent family member(s)			Publication date
FR	A	2804471	2001-08-03	US	B	6729388	2004-05-04
				US	A	2001027857	2001-10-11
				DE	A	10102088	2001-08-16
JP	A	10122787 A2		none			
SU	A	556311	1977-04-30	none			